

## VIA Connect<sup>2</sup>

Wireless Content Presentation, Collaboration, and Conferencing Solution | HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)



VIA Connect<sup>2</sup> is a smart, secure, wireless and wired presentation and collaboration platform that makes it simple to get actual work done during meetings and classes. With most laptops or mobile devices, users can view, edit, and comment on documents in real-time sessions.

Kramer's new VIA 4.0 is all about the end user. The new VIA application UI is intuitive, user-friendly and much easier to use. VIA 4.0 enables any user, including guests, to easily and securely connect and automatically disconnect at the end of the session. Meeting participants can display or stream full, uninterrupted video from their device, and even play YouTube® videos in full frame rate. Up to four participants can share their screens simultaneously on the main display either using the VIA app mirroring feature, iOS mirroring via AirPlay™, Windows & Android mirroring via Miracast™, or ChromeBook mirroring. The shared screen sizes are automatically adjusted based on their respective source, and can be resized manually by the user when needed. The platform can handle most small to medium size meeting spaces and is ideal for classrooms and huddle spaces. VIA Connect<sup>2</sup> is super-compact (74x74mm) with flexiblity to install with both built-in Wi-Fi and LAN connectivity and includes industry-leading 1024-bit encryption for secure use on the internal network

## **FEATURES**

3rd party Security Certification

Built-In isolated Wi-Fi and LAN

Quick and Reliable Wireless Connectivity - A simple and intuitive user interface enables iOS™, Android™, Chromebook™, PC, and Mac™ device users to instantly connect to a main display. 2.4GHz/5GHz Wi-Fi and MIMO antennas establish and maintain a fast and reliable connection

Automatically stops presentation when leaving the room

Clientless Connectivity - Airplay, Miracast, Join Through Browser

Optimized for Video Conferencing - Room devices driver feature allows users to wirelessly connect to the professional grade camera and AV in their meeting spaces easily and instantly

Calendar widget on the wallpaper for instant connectivity within one click

3rd Party Web Applications - Run directly from the device without needing to use the application Powerful Security Feature - 802.1x User authentication, 1024-bit encryption, dynamic room code Built-In Wi-Fi and LAN

Comprehensive Collaboration Functionality - Whiteboard, filesharing, View Main Display, chat, etc High-Quality Video Streaming - Supports up to 4K@60Hz resolution using the VIA app Multimedia feature

Simultaneous Display - Four participants can simultaneously present content on the main display Seamless Live Video Streaming - Stream live content from meeting rooms, classrooms and studios using RTMP/RTMPS to all the leading platforms, like YouTube™, Kaltura™, Panopto™ and more Up to 4K@60 HDMI Wired Input - Enables hard–wiring, auto switching, for connecting a computer or any HDMI compatible device camera, multimedia player or computer that supports HDCP signals Wireless USB - Supports Microphone, Speaker & Camera

Cloud-Based Management - Seamlessly compatible with VIA Site Management (VSM) Easy and Flexible Installation - With a super-compact form factor, it can be discreetly installed on the back of a display, projector or almost anywhere



## TECHNICAL SPECIFICATIONS

Ports 1 Ethernet: On an RJ-45 connector

2 USB 3.0: On a female USB type-A connector

1 USB 2.0: On a female USB type-A connector

2 Pin connector: Video Switching control

Outputs 1 HDMI 2.0 :

Inputs 1 HDMI 2.0 :

Video Max Resolution: up to 4K@60 for both Input & Output

Web Conferencing Cameras Tested with VIA Versa Feature Logitech MeetUp, Logitech C270, Logitech BCC950, Logitech C525, Logitech Brio UHD PRO, Logitech C310, Logitech C922, Avaya HC020, Avaya HC050, Huddly GO, Minrray MG100A, Microsoft Livecam HD-3000, TedGem 1080p, Vaddio HuddleSHOT, Yealink UVC80, Bose Videobar VB1, BIAMP Devio SCR-20, BIAMP Devio

SCR-25,LUMENS B10U, LUMENS B11U, LUMENS B2U, MAXHUB — UCS10, Aver

CAM340+, Aver VB342+, Yealink UVC30ROOM, Aver CAM340+, Avonic

AV-CM44-VCUC-B PTZ, Konftel C50 PTZ

Video Conferencing Apps Tested with VIA Versa Feature Teams and Zoom

All brand names, product names, and trademarks are the property of their

respective owners

Audio Web Conferencing Audio Devices Tested with VIA Versa Feature: Aver VB432

Speaker (Microphone), Yamaha YVC-330 (Speaker, Microphone, Bluetooth phone gateway), Yamaha YVC-1000 (Speaker, Microphone, Bluetooth phone gateway),

Nureva HDL300 (Speaker)

General Processor: Intel® Gemini Lake QC SOC

Memory: 4GB LPDDR4 (2400)

Storage: 32GB eMMC

Networking: 1 x Gigabit LAN Wi-Fi 802.11 ac/b/g/n dual band

Operating System: Linux

Power Input Source: 12V DC

Consumption: 1.3A

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Regulatory Compliance (Standards Compliance) Safety: CE

Enclosure Type: Aluminum

Cooling: Fan with sink

Kensington lock:

Accessories Included: Power adapter, Video Switching control cable, VESA mount

Product Dimensions 7.30cm x 7.30cm x 3.34cm (2.87" x 2.87" x 1.31" ) W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions  $15.70 \, \text{cm} \times 12.00 \, \text{cm} \times 8.70 \, \text{cm} (6.18" \times 4.72" \times 3.43") \, \text{W, D, H}$ 

Shipping Weight 0.6kg (1.3lbs) approx



